

## DATASHEET

## 3M DBI SALA EXOFIT XE50 POSITIONING HARNESS SIZE 2



3M™ DBI-SALA® ExoFit™ XE50 Positioning Safety Harness with pass-through buckles.

The 3M™ DBI-SALA® ExoFit™ XE50 is designed with high-quality components specially developed for enhanced safety and fit while working at heights.

Built with durable 26kN polyester webbing and alloy steel hardware, 3M™ DBI-SALA® ExoFit™ XE50 was created to endure the daily conditions of your job site.

- Cross Chest Buckle assembly for central front fall arrest attachment point optimised position on body.
- Revolving torso adjusters (patented) for quick and easy harness fit and adjustment.
- Rear Large D-Ring, Front Standard D-Ring, Work Positioning Large Cranked D-Ring attachment points.
- Waist Padding Optional comfort padding is available as accessory (order separately). Optional shoulder pads have yoke design to reduce uncomfortable chaffing to the neck.
- Integrated pSRL tunnel lets you quickly and easily connect and disconnect personal SRLs.
- Suspension trauma relief straps with low-profile design included.
- Steel hardware.
- Equipped with auto-resetting and re-positionable lanyard keepers for fast and easy parking of snap hooks and carabiners.
- 3M™ Connected Safety ID (RFID) integrated for simplified inventory, inspection, and record management.

Industry: Construction, General Industrial, General Manufacturing, Transportation
Max Weight: 140 kg

EN358:2019 CE EN361

