



BEESWIFT[®]
FOCUSED ON SAFETY

Product Code

CARC7SYN38



Anti Static



Arc Flash Protection



Cat 3 - High Risk



Fire Retardant



Hi Visibility



Protection for Welding and Allied Processes

DATASHEET

ARC COMPLIANT C/ALL SY/N 38



- Fire Retardant, Hi Vis, Anti-static, ARC Flash coverall.
- 300gsm 60/40 Modacrylic/cotton blend.
- Inherently flame retardant.
- Fire Retardant properties will not diminish with repeated laundering.
- Triple stitch construction.
- 2 hip pockets.
- Large bellows pocket to each leg with hook and loop closure flap.
- Right leg mobile phone pocket with hook and loop closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.

- EN ISO 13688:2013 - General requirements for protective clothing
- EN ISO 20471:2013 Class 3 - Test method for high visibility
- EN 1149-5:2018 - Anti Static - Material performance and design requirements
- EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
- EN ISO 11612:2015 (A1 A2 B1 C1 F1) - Protection against heat and flame

ARC FLASH

EN 61482-2:2020 - Performance requirements and design requirements
(ELIM = 14 Cal/cm²)
(ATPV = 17 Cal/cm²)

