



**BEESWIFT®**  
FOCUSED ON SAFETY

Product Code

COC40Y3XL



Anti Static



Cat 3 - High Risk



Conforms to the correct EN standards



Chemical Hazards



Limited Chemical Splash Protection



Garment comes with a hood



Pressurised Jet of Liquid Chemical Protection



Infective Agents Protection



Noxious Dust



Radioactive Contamination Protection



Liquid Spray Aerosol (unpressurised) Protection

## DISPOSABLE COVERALL YELLOW 3XL MICROPOROUS TYPE 3/4/5/6



Microporous type 3/4/5/6 disposable coverall

- 90gm 56% SMS polypropylene, 44% polyethylene
- Polyethylene laminated +3 layers of polypropylene
- Ultrasonic taped seams
- Elasticated hood, wrists, ankles and waist
- Zip front with storm flap
- Elasticated thumb loops

Ideal uses:

- Maintenance & Repair
- Powder coating
- Insulation laying
- Pharmaceutical manufacture
- Paint spraying
- Wood & Metal processing
- Low level chemical handling
- Resin application
- Pressure/Steam water cleaning
- Fibreglass manufacture

- Conforms to:  
EN ISO 13688:2013+A1:2021

EN 14605:2005+A1:2009 (Type 3B & 4B)

EN ISO 13982-1:2004+A1:2010 (Type 5B)

EN 13034:2005+A1:2009 (Type 6B)

EN 1073-2:2002 (Class 2)

EN 14126:2003+AC:2004

Resistance to Penetration by contaminated liquids  
under hydrostatic pressure = Class 6

Resistance to Penetration by infective agents due to  
mechanical contact with substances containing contaminated liquids =  
Class 6

Resistance to penetration by contaminated liquid aerosols = Class 3  
Resistance to penetration by contaminated solid particles = Class 3

EN 1149-5: 2018

EN 14325:2004

